

A	Dept	1	2	3	4	5	6	7	8	A
	Qty	1								
	DC	1								
	ED	1								
	IE	1								
	ISO	1								
	PD	1								
B	R&D	1								B
	SD	1								
	QA	1								
	QC	1								
C	QE	1								C
D										D
E										E
F										F
G										G
H										H

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use of this information in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

N=No.of contacts/2

W/ Pick up  
Scale 1:2

W/ Mylar  
Scale 1:2

DS1026-07 - X X X X X X X

- Pick up support
- S:W/ Pick up
- X:W/O Pick up
- M:W/ Mylar
- Packing type
- B:Tube
- R:Tape on reel
- Post support
- S:W/ Post
- X:W/O Post
- Mounting type
- S:SMT type
- Housing color
- B:Black
- Contact plating
- 8: Full gold flash
- Connector type
- S:Socket
- No.of contacts
- 2x2~2x40

(Series Image-Reference Only)

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE	2.00mm Female Header Double Row SMT W/ Post Type	
X.	±0.60	X.	±5°	mm			
.X	±0.38	.X	±3°	A4	SHEET	DS1026-07 SERIES	
.XX	±0.25	.XX	±2°	<b>晨翔电子有限公司</b> <b>CONNFLY CONNELY ELECTRONIC CO. LTD</b>			
DRAWING TYPE		CUSTOMER					
SCALE		1:1 SHEET 1 OF 1					
DRAWING NO.		C-DS1026-07-XXXXXXX-D					

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 07/27/10'		LJC 07/27/10'
B	DRAWING UPDATE	JLZ 08/19/16'	HZW 08/19/16'	LJC 08/19/16'
C	DRAWING UPDATE	JLZ 08/01/18'		
D	DRAWING UPDATE	JLZ 05/16/25'		

Notes:

Specifications:

- Contact Resistance: 20mΩ Max.
- Insulation Resistance: 1000MΩ Min.
- Dielectric Withstanding Voltage: 500V AC(rms) For 1 Minute.
- Current Rating:1.5A.
- Temperature: -40°C~+105°C.

Materials:

- Contact Material: Copper Alloy.
- Contact Plating: Gold Plating Over Nickel.
- Insulator Material: High temp,Black,UL94-V0.

Product Number Code: