



The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNLY Electronic Co., Ltd. are reserved. This drawing is for reference purposes only and does not constitute authorization of its use in any format or manner. CONNLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Male



Female



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 02/08/25'		

NOTE:

- 1.Rated voltage:400/500V
- 2.Rated current:5/15/30A
- 3.Insulation resistance:2000MΩ
- 4.Withstand voltage:1500V
- 5.Operating temperature: -25℃ to +85℃
- 6.Wiring method: Solder
- 7.Mating cycle: 500 cycles
- 8.Cable diameter:7-12mm

Materials:

- 1.Shell material: PPO,PA66,UL94V-0
- 2.Insulation material: PPS
- High temperature resistance 260℃
- 3.Contact material: Brass with gold plating

Product Number Code:


DS1110-26-X X X X X

Install Type:
A:Docking type
Contact Plating:
8:Gold flash
Color of nut:
U:Blue
Color of housing:
B:Black
No. of Contacts:
02 03 04 05A 05C 6 7 9


GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	21mm Waterproof aviation plug (Solder type)	
X.	±0.60	X.	±5°	UNITS	mm			
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1110-26 Series	
.XX	±0.25	.XX	±2°					
DRAWING TYPE		CUSTOMER		 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
SCALE		1:1	SHEET					1 OF 6
DRAWING NO.		C-DS1110-26-XXXXX-A						

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNELY Electronic Co., Ltd. are reserved. This drawing is for reference purposes only and does not constitute authorization of its use in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Male



Female



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 02/08/25'		

NOTE:

- 1.Rated voltage:400/500V
- 2.Rated current:5/15/30A
- 3.Insulation resistance:2000MΩ
- 4.Withstand voltage:1500V
- 5.Operating temperature: -25℃ to +85℃
- 6.Wiring method: Solder
- 7.Mating cycle: 500 cycles
- 8.Cable diameter:7-12mm

Materials:

- 1.Shell material: PPO,PA66,UL94V-0
- 2.Insulation material: PPS
- High temperature resistance 260℃
- 3.Contact material: Brass with gold plating

Product Number Code:

DS1110-26-XXXXXX

- Install Type:
B:Rear nut type
Contact Plating:
8:Gold flash
Color of nut:
U:Blue
Color of housing:
B:Black
No. of Contacts:
02 03 04 05A 05C 6 7 9

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	21mm Waterproof aviation plug (Solder type)	
X.	±0.60	X.	±5°	UNITS	mm			
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1110-26 Series	
.XX	±0.25	.XX	±2°					
DRAWING TYPE		CUSTOMER		 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
SCALE		1:1	SHEET					2 OF 6
DRAWING NO.		C-DS1110-26-XXXXX-A						





晨翔电子有限公司


CONNELY CONNELY ELECTRONIC CO. LTD

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNELY Electronic Co., Ltd. are reserved. This drawing is for reference purposes only and does not constitute authorization of its use in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Male



SECTION A-A



NOTE:

- 1.Rated voltage:400/500V
- 2.Rated current:5/15/30A
- 3.Insulation resistance:2000MΩ
- 4.Withstand voltage:1500V
- 5.Operating temperature: -25℃ to +85℃
- 6.Wiring method: Solder
- 7.Mating cycle: 500 cycles
- 8.Cable diameter:7-12mm

Materials:





- 1.Shell material: PPO,PA66,UL94V-0
- 2.Insulation material: PPS
- High temperature resistance 260℃
- 3.Contact material: Brass with gold plating

Product Number Code:



DS1110-26-XXXXX

- Install Type:
 - C:Flange type
- Contact Plating:
 - 8:Gold flash
- Color of nut:
 - U:Blue
- Color of housing:
 - B:Black
- No. of Contacts:
 - 02 03 04 05A 05C 6 7 9

Female



Panel cutout
Plate thickness ≤3mm



SECTION B-B

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	3 OF 6
DRAWING NO.	C-DS1110-26-XXXXX-A		



PROJECTION	TITLE	21mm Waterproof aviation plug (Solder type)
UNITS	mm	
SHEET SIZE	A4	SERIES DS1110-26 Series




晨翔电子有限公司
CONNELY CONNELY ELECTRONIC CO. LTD

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNELY Electronic Co., Ltd. are reserved. This drawing is for reference purposes only and does not constitute authorization of its use in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Male



SECTION A-A



NOTE:

- 1.Rated voltage:400/500V
- 2.Rated current:5/15/30A
- 3.Insulation resistance:2000MΩ
- 4.Withstand voltage:1500V
- 5.Operating temperature: -25℃ to +85℃
- 6.Wiring method: Solder
- 7.Mating cycle: 500 cycles
- 8.Cable diameter:7-12mm

Materials:


- 1.Shell material: PPO,PA66,UL94V-0
- 2.Insulation material: PPS
- High temperature resistance 260℃
- 3.Contact material: Brass with gold plating

Product Number Code:



DS1110-26-XXXXX

- Install Type:
D:Square disc type
Contact Plating:
8:Gold flash
Color of nut:
U:Blue
Color of housing:
B:Black
No. of Contacts:
02 03 04 05A 05C 6 7 9

Female



Panel cutout
Plate thickness ≤3mm




SECTION B-B

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	4 OF 6
DRAWING NO.	C-DS1110-26-XXXXX-A		

PROJECTION	TITLE	21mm Waterproof aviation plug (Solder type)	
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1110-26 Series
 晨翔电子有限公司 CONNELY CONNELY ELECTRONIC CO. LTD			

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights are reserved by CONNELY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Male



NOTE:

- 1.Rated voltage:400/500V
- 2.Rated current:5/15/30A
- 3.Insulation resistance:2000MΩ
- 4.Withstand voltage:1500V
- 5.Operating temperature: -25℃ to +85℃
- 6.Wiring method: Solder
- 7.Mating cycle: 500 cycles
- 8.Cable diameter:7-12mm

Materials:


- 1.Shell material: PPO,PA66,UL94V-0
- 2.Insulation material: PPS
- High temperature resistance 260℃
- 3.Contact material: Brass with gold plating

Product Number Code:

DS1110-26-X X X X X

- Install Type:
E:Front nut type
Contact Plating:
8:Gold flash
Color of nut:
U:Blue
Color of housing:
B:Black
No. of Contacts:
02 03 04 05A 05C 6 7 9

Female



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	4 OF 6
DRAWING NO.	C-DS1110-26-XXXXX-A		

PROJECTION	TITLE	21mm Waterproof aviation plug (Solder type)	
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1110-26 Series
 晨翔电子有限公司 CONNELY CONNELY ELECTRONIC CO. LTD			

A	B	C	D	E	F	G	H	Dept	Qty
								DC	1
								ED	1
B	C	D	E	F	G	H	IE	1	
							ISO	1	
							PD	1	
C	D	E	F	G	H	R&D	1		
						SD	1		
						QA	1		
D	E	F	G	H	QC	1			
					QE	1			

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 02/08/25'		

Solder contact arrangement and spec

No.of Contacts	2	3	4	5A	5C	6	7	9
Malc contact face view								
Rated current (A)	30A	30A	30A	30A	15A	15A	15A	5A
Contact diameter	Ø2.8*2	Ø2.8*3	Ø2.8*4	Ø2.8*5	Ø1.8*5	Ø1.8*6	Ø1.8*7	Ø1.0*9
Wiring method	Solder							
Woring Voltage(AC.V)	500V	500V	500V	500V	500V	500V	500V	400V
Test Voltage(AC.V)1min	1500V	1500V	1500V	1500V	1500V	1500V	1500V	1500V
Contact resistance(mΩ)	1mΩ	1mΩ	1mΩ	1mΩ	2.5mΩ	2.5mΩ	2.5mΩ	5mΩ
Wire Size(mm²/AWG)	≤4.17/11	≤4.17/11	≤4.17/11	≤4.17/11	≤2/14	≤2/14	≤2/14	≤0.785/18

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	21mm Waterproof aviation plug (Solder type)	
X.	±0.60	X.	±5°	UNITS	mm			
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1110-26 Series	
.XX	±0.25	.XX	±2°	 晨翔电子有限公司 CONNFLY CONNPLY ELECTRONIC CO. LTD				
DRAWING TYPE		CUSTOMER						
SCALE	1:1	SHEET	6 OF 6					
DRAWING NO.	C-DS1110-26-XXXXX-A							