



















Reference to female R/A type					Reference to female R/A type				
Pitch	Position	Row with conntacts	column with conntacts	Contact Arrange	Pitch	Position	Row with conntacts	column with conntacts	Contact Arrange
2.54	96 (3*32)	abc	1-2-3		2.54	48 (3*16)	abc	1-2-3	
		abc	1-3				abc	1-3	
		abc	2-4				abc	2-4	
		ac	1-2-3				ac	1-2-3	
		ac	1-3				ac	1-3	
		ac	2-4				ac	2-4	
		a	1-2-3				a	1-2-3	
		a	1-3				a	1-3	
		a	2-4				a	2-4	

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE
X.	±0.60	X.	±5°	UNITS	mm	DIN 41612 C & RTYPE (3ROWS)
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES DS1120 SERIES
.XX	±0.25	.XX	±2°			
DRAWING TYPE		CUSTOMER				
SCALE		1:1	SHEET	2 OF 2		
DRAWING NO.		C-DS1120-XXXXXXX-B				
		 晨翔电子有限公司				
		CONNFLY CONNFLY ELECTRONIC CO., LTD				