	1		2	ĺ	3	4		5	6		7 1	8	
	ept							REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED	
	Qty							A	NEW RELEASE	JLZ 08/04/23'			
						1				, , ,			
E													-
	0 1												_
PI	D 1			₩.4!}		<u> </u>	-						_
R	&D 1				/								
SI	D 1					U U		Notes:					
BQ	A 1			A Loc	le Nu+	B Washer		Specific	cations:				В
Q				A LUC	K NUL	D Washer			perature: -20°C~+80°C	D.			
	E 1							Materia	ls:				
te —	d use right			1777	773	7.7.7.7	THE			nade of Nylon or PP;Pa	rts B and D are made	of NBR.	
i pup	such				Mining and a second		***K		t Number Code:				
ies	of s			~				DS1	170-01 - <u>X X X</u>				
opert	aiver diver	Assem	nbled	⊐  + <del>      </del> -					TTT				
C   E	indicates. Unauthorized use constitute authorization of atte a waiver of such rights.			·└──└──────────────────────────	▝↓↓↓↓↓					Materials type			С
lectu	of ct litute			_L2_						N: Nylon P: PP			
intel	es n consi consi				4.4	D Seal E S	Sealing Nut			— Color			
The	id do			C Boo	, y					A: Gray B: Black			
oited.	conn does	Madal		Thread O.D.I.4(mm)	Thread Longth 1.0(mm)					-			
rohib	vely by CONNFL oses only and rights does no	Model PG7	Cable Range(mm) 3~6.5	Thread O.D.L1(mm) 12.5	Thread Length L2(mm)	Spanner Size A&E(mm) 18/16				— Model PG7 PG7S PG9 P	0005		
.≊	poset righ	PG7 PG7S	3~6.5	12.5	9	18/16					692		
pient   [	such	PG75 PG9	2~3 4~8	12.5	9	22/19				 PG63 PG63S			D
reci	rcise	PG9S	2~6	15.2	9	22/19							
1 the	exe	PG11	5~10	18.6	9	24/22							
than	s for over to	PG11S	3~7	18.6	9	24/22							
other	dela;	PG13.5	6~12	20.4	10	27/24							
Ity o	ties provided herein are tries provided herein are tries or delays scretton; failures or delays	PG13.5S	5~9	20.4	10	27/24							
0 0	ded	PG16	10~14	22.5	10	30/27							
¢ E	provi fr	PG16S	7~12	22.5	10	30/27							E
- Insol	ties	PG19	10~15	24	10	30/28							
discl	roper dis	PG19S	10~12	24	10	30/28							
Any	ad p.	PG21	13~18	28.3	12	35/33			Marcal Control of Cont				
ntial.	at its	PG21S	9~16	28.3	12	35/33							
nfide	s, tro	PG25	16~21	30	12	37/35			10				
c s	ty right:	PG25S	13~18	30	12	37/35							
F	oper	PG29 PG29S	18~25 13~20	37 37	12	45/42 45/42		54.101					F
Ltd.	al CO	PG295 PG36	22~32	47	12 15	45/42 58/52							'
Co.,	pate fror illectu	PG36 PG36S	22~32	47	15	58/52							
, ji	arks, nsent i intel	PG42	32~38	54	18	62/58							
	n coin coints	PG42S	25~31	54	18	62/58							
ü ۲	o, tr writte enforc	PG48	37~44	59.3	18	70/64		Series Image-Refe	rence Only)				
ONNF	Tor te	PG48S	29~35	59.3	18	70/64							
G	· 프 프 프 프 프 프 프 프 프 프 프 프 프 프 프 프 프 프 프	PG63	42~50	71	30	83/77							G
fron	witho	PG63S	32~40	71	30	83/77							-
.≊. ⊒.	r. oc					GENERAL T	OLERANCE	ANGLE TOLERA	NCE PROJECTION				$\neg$
herei	rohib										Plastic fixed cab	le gland PG type	
ided	or r					X.	±0.60	X. ±5°		A4 SERIES	DS1170-01 SEF		-
prov	stric mat					.X.	±0.38	.X ±3° .XX ±2°	SHEET SIZE	A4 SERIES	USII/U-UI SEF	NILO	_
ation	y for						±0.25			E ¥11 H			
L  u	icatic icatic n an					DRAWING T				晨翔电	丁佰№	さ公 可	Н
<u>2</u> .   ٦   چ	the provided of the provided but not infruited to, traderry or modification is strictly provibilitied without prove written co. Its use in any format or manner. CONNFLY may enforce its use in any format or manner.					SCALE	1:1	SHEET 1 OF		CONNFLY E			
F I	righ its -					DRAWING N	10. C-DS	51170-01-XXX-A		CONNELYE	LECIKUNIC	GO. LID	
	1		2		3	4	· · · ·	5	6		7	8	